


: SS-40VA-T50B
: 40W LED
: V00
: 2021-12-06



DRIVER

ED DRIVER



SS-40VA-T50B LED



	100Vac		277Vac	
	90Vac		305Vac	
	47Hz	50/60Hz	63Hz	
			0.5A	100Vac
			0.18A	277Vac
			50W	100Vac
(120Vac)			50A	
(220Vac)			65A	
(277Vac)			75A	
			3W	220Vac/50Hz
	0.95	0.97		220Vac/50Hz,
	0.90			100-277Vac/50Hz, 80-100%
		12%	15%	220Vac/50Hz,
			20%	100-277Vac/50Hz, 80-100%




SS-40VA-T50B LED

	28V		50V	28-36V
	36V		50V	$P_o = V_o \cdot I_o = 40W$
	0.8A		1.1A	1.1A 36V 0.8A 50V
AOC	0.64A		1.1A	
			60V	
@ 120Vac	85.0%	87.0%		50V/0.8A
@ 220Vac	87.0%	89.0%		50V/0.8A
@ 277Vac	86.0%	88.0%		50V/0.8A
	-8%		+8%	
PK-AV		100%	150%	
			10%	
			1.0S	120Vac,
			0.5S	220Vac,
	-8%		+8%	
	-8%		+8%	
	-0.07%/		+0.07%/	0 90
			5W	



















SS-40VA-T50B LED



1 , , 704

2

- mm) : × × =495×385×162

- 42

- 0.415kg 18.9kg

-

GB 3873 83

1

RoHS

RoHS (2011/65/EU)

2015/863/EU



SS-40VA-T50B LED



V00		2021/12/06	

