:SS-200EUH-XX

: 200

SS-200EUH





产品特性:

□ 89%

□ 115VAC 230VAC

□ 全方位保护:短路/过温/ /过

0

□ 质保3年

产品描述:

SS-200EUH 200W 115Vac 230Vac 30mm

型号列表:


型号		最大输出 功率			()	
SS-200EUH-12	100-120Vac 200-240Vac	200W	12V	0-17A	85%	75
SS-200EUH-24	100-120Vac 200-240Vac	200W	24V	0-8.8A	88%	75
SS-200EUH-36	100-120Vac 200-240Vac	200W	36V	0-5.9A	89%	75
SS-200EUH-48	100-120Vac 200-240Vac	200W	48V	0-4.4A	89%	75

SS-200EUH-XX

220Vac , 25℃

115VAC 230VAC),





输入性能:

参数	最小值	典型值	最大值	
	100Vac		120Vac	
	180¥ac		2 64Vac	
	47Hz		68Hazc	
			4.5A	5100Vac
(115Vac)			100A	冷枫 唐
			1V51VAC	220Vac/50Hz


86-755-29358800

1

TOA2 I I î


输出性能(SS-200EUH-12):


参数	最小值	典型值	最大值	备注
		12V		
空	11V		13V	
			17A	
			200W	
	83.0%	85.0%		@ 220Vac
	82.0%	84.0%		@ 110Vac
	-1%		+ 1%	
PK-PK			1%	, 20MHz
	-1%		+1%	
	-1%		+ 1%	
			10%	
	-10%		+ 10%	10% - 50% 100% - 50%
		15	2S	
		50mS		@ 220Vac
		16mS		@ 220Vac



输出性能(SS-200EUH-24):


参数	最小值	典型值	最大值	备注
		24V		
空	22V		26V	
			8.8A	
			200W	
	86.0%	88.0%		@ 220Vac
	84.0%	86.0%		@ 110Vac
	-1%		+ 1%	
PK-PK			1%	, 20MHz
	-1%		+1%	
	-1%		+ 1%	
			10%	
	-10%		+ 10%	10% - 50% 100% - 50%
		15	2S	
		50mS		@ 220Vac
		16mS		@ 220Vac






输出性能(SS-200EUH-36):

参数	最小值	典型值	最大值	备注
		36V		
空	34V		38V	
			5.9A	
			200W	
	86.0%	88.0%		@ 220Vac
	84.0%	86.0%		@ 110Vac
	-1%		+ 1%	
PK-PK			1%	, 20MHz
	-1%		+1%	
	-1%		+ 1%	
			10%	
	-10%		+ 10%	10% - 50% 100% - 50%
		15	2S	
		50mS		@ 220Vac
		16mS		@ 220Vac





5:	
	@ 100%ac 0
	+%%
	191%% 4

其他性能:



环境要求:

参数	最小值	典型值	最大值		备注
Та	20	25	. 50		
l d	-20	25	+50		
	-25	25	+ 85		
	20%RH		90%RH		
	10%RH		95%RH		
			2000m	>2Km	5 /1Km

安规标准:


认证	安规标准	认证状况	备注
UL/cUL	UL60950-1		
CCC	GB 4943.1-2011		







特性曲线:

50) Vs.



Vs.





SS-200EUH

结构尺寸特性(单位:mm)







```
e 装 mm): × × = 495×385×162;
- 12
- 0.69kg 9.8kg
- •
```

变更履历表

V00	2022/02/16	
V01	2022/04/14	

